

新产品测试表 型号：ZP15-S05

日期：2019-6-28

制表：曾德红

输入电压	输入电流	输入功率	输出负载		输出电压	效率	纹波	短路启动/过流点	VCC电压	负载调整率	电压调整率	电压精度	备注
90V			空载		4.99		/		11.1	0.40%	0.80%	-0.60%	
	0.038	1.75	10%	0.30	4.99	85.5%	68	OK	13.95				
	0.07	3.47	20%	0.60	4.99	86.3%	86	OK	14.7				
	0.101	5.22	30%	0.90	4.99	86.0%	50-108	OK	15.37				
	0.132	6.97	40%	1.20	4.99	85.9%	50-122	OK	15.67				
	0.163	8.75	50%	1.50	4.99	85.5%	50-140	OK	15.92				
	0.193	10.5	60%	1.80	4.99	85.5%	50-150	OK	16.16				
	0.223	12.3	70%	2.10	4.99	85.2%	50-152	OK	16.42				
	0.252	14.4	80%	2.40	4.99	83.2%	50-160	OK	16.6				
	0.285	16	90%	2.70	4.99	84.2%	50-175	OK	16.95				
0.317	18	100%	3.00	4.98	83.0%	50-175	OK 4.5A 0W	17.4					
115V			空载		4.99		/		10.93	0.40%	0.80%	-0.60%	
	0.031	1.75	10%	0.30	4.99	85.5%	64	OK	14.13				
	0.057	3.44	20%	0.60	4.99	87.0%	68	OK	14.7				
	0.082	5.15	30%	0.90	4.99	87.2%	50-90	OK	15.5				
	0.107	6.89	40%	1.20	4.99	86.9%	50-108	OK	15.79				
	0.131	8.63	50%	1.50	4.99	86.7%	50-126	OK	16.06				
	0.155	10.3	60%	1.80	4.99	87.2%	50-142	OK	16.3				
	0.179	12.1	70%	2.10	4.98	86.4%	50-148	OK	16.54				
	0.203	13.8	80%	2.40	4.99	86.8%	50-154	OK	16.75				
	0.227	15.6	90%	2.70	4.99	86.4%	50-160	OK	16.99				
0.251	17.4	100%	3.00	4.97	85.7%	50-170	OK 4.7A 0W	17.3					
230V			空载		4.99		/		11.3	0.40%	0.80%	-0.60%	
	0.017	1.98	10%	0.30	4.99	75.6%	50	OK	13.21				
	0.03	3.54	20%	0.60	4.99	84.6%	74	OK	14.59				
	0.042	5.18	30%	0.90	4.99	86.7%	84	OK	15.61				
	0.054	6.87	40%	1.20	4.99	87.2%	50-104	OK	16.22				
	0.066	8.54	50%	1.50	4.99	87.6%	50-120	OK	16.49				
	0.078	10.2	60%	1.80	4.99	88.1%	50-136	OK	16.75				
	0.09	12	70%	2.10	4.99	87.3%	50-146	OK	16.98				
	0.101	13.6	80%	2.40	4.99	88.1%	50-156	OK	17.22				
	0.113	15.4	90%	2.70	4.99	87.5%	50-166	OK	17.46				
0.124	17.1	100%	3.00	4.97	87.2%	50-180	OK 5.0A 2.77W	17.68					

