

广州中逸光电子科技有限公司

测试报告 (Inspection report)

产品型号: SDM60-S24		批号:		日期: 2016-8-8		仪器编号: LW2676;ADS1062C					
1. 耐压测试											
Input to Output <u>3000</u> VAC Leakage current <u>0.8</u> mA at 1 min OK!											
2. 测试数据											
输入			输出								
U _{in} (VAc)	I _{in} (A)	P _{in}	U _{out} (V)	I _{out} (A)	P _{out}	效率	纹波噪声 (mV)	电压精度	电压调整率	负载调整率	
100	最小载	0.129	6.95	24.070	0.250	6.02	86.58%	30	-0.13%	0.04%	0.42%
	半载	0.523	34.00	24.020	1.250	30.03	88.31%	30			
	满载	1.033	69.30	23.970	2.500	59.93	86.47%	60			
140	最小载	0.104	7.00	24.060	0.250	6.02	85.93%	40			
	半载	0.405	33.70	24.030	1.250	30.04	89.13%	50			
	满载	0.760	68.00	23.960	2.500	59.90	88.09%	65			
240	最小载	0.088	7.29	24.070	0.250	6.02	82.54%	70			
	半载	0.299	34.10	24.030	1.250	30.04	88.09%	70			
	满载	0.537	67.80	23.970	2.500	59.93	88.38%	80			
								测试结果	符合技术手册参数要求 pass		
3. 稳定性											
Vout	100%-0%-100%load			启动模式	turn on			测试结果	符合技术手册参数要求 pass		

测试	姚桂花2016-8-8	审核	谢洪发 2016-8-8	批准	罗胜东 2016-8-8
----	-------------	----	--------------	----	--------------