

# 广州中逸光电子科技有限公司

## 测试报告 (Inspection report)

产品型号: ZP06-S12		批号:		日期: 2017-3-31		仪器编号: LW2676;ADS1062C						
1. 耐压测试												
Input to Output <u>4000</u> VAC Leakage current <u>0.53</u> mA at 1 min OK!												
2. 测试数据												
输入			输出									
U <sub>in</sub> (VAC)	I <sub>in</sub> (A)	P <sub>in</sub>	U <sub>out</sub> (V)	I <sub>out</sub> (A)	P <sub>out</sub>	效率	纹波噪声 (mV)	电压精度	电压调整率	负载调整率		
100	最小载	0.015	0.84	11.980	0.050	0.599	71.31%	28	-0.16%	0.05%	0.02%	
	半载	0.065	3.74	11.979	0.250	2.995	80.07%	22				
	满载	0.123	7.46	11.975	0.500	5.988	80.26%	24				
140	最小载	0.014	1.01	11.981	0.050	0.599	59.31%	22				
	半载	0.048	3.73	11.980	0.250	2.995	80.29%	32				
	满载	0.088	7.35	11.979	0.500	5.990	81.49%	30				
240	最小载	0.013	1.35	11.984	0.050	0.599	44.39%	36				
	半载	0.032	4.07	11.983	0.250	2.996	73.61%	30				
	满载	0.059	7.60	11.981	0.500	5.991	78.82%	28				
								测试结果	符合技术手册参数要求 pass			
3. 稳定性												
Vout	0%-100%load			启动模式	turn on			测试结果	符合技术手册参数要求 pass			

测试	姚桂花2017-3-31	审核		批准	罗胜东 2017-3-31
----	--------------	----	--	----	---------------