

# 广州中逸光电子科技有限公司

## 测试报告 (Inspection report)

产品型号: ZP10-S09		批号:		日期: 2016-6-27		仪器编号: LW2676;ADS1062C						
1. 耐压测试												
Input to Output <u>4000</u> VAC Leakage current <u>0.48</u> mA at 1 min OK!												
2. 测试数据												
输入				输出								
U <sub>in</sub> (VAC)	I <sub>in</sub> (A)	P <sub>in</sub>	U <sub>out</sub> (V)	I <sub>out</sub> (A)	P <sub>out</sub>	效率	纹波噪声 (mV)	电压精度	电压调整率	负载调整率		
100	最小载	0.019	1.29	8.982	0.110	0.988	76.59%	60	-0.26%	0.04%	0.04%	
	半载	0.056	6.10	8.981	0.550	4.940	80.98%	45				
	满载	0.097	12.50	8.981	1.110	9.969	79.75%	50				
140	最小载	0.023	1.32	8.982	0.110	0.988	74.85%	60				
	半载	0.078	6.09	8.980	0.550	4.939	81.10%	50				
	满载	0.143	12.30	8.978	1.110	9.966	81.02%	48				
240	最小载	0.027	1.53	8.980	0.110	0.988	64.56%	58				
	半载	0.101	6.43	8.979	0.550	4.938	76.80%	64				
	满载	0.189	12.50	8.977	1.110	9.964	79.72%	30				
								测试结果	符合技术手册参数要求 pass			
3. 稳定性												
Vout	0%-100%load		启动模式		turn on		测试结果	符合技术手册参数要求 pass				

测试	姚桂花 2016-6-27	审核	谢洪发 2016-6-27	批准	罗胜东 2016-6-27
----	---------------	----	---------------	----	---------------